

Page	Item	Change
12	2, Exhaust Smoke (Diesel)	Where available, the manufacturer's specification is used for the smoke meter test.
14	3, Exhaust CO/HC/Lambda	Where available, the manufacturer's specification is used for the emissions tests.
19	7, Seats	The driver's seat must be adjustable as designed and manufactured.
38	21, Service Brake Performance	For vehicles registered on or after 28 July 2010 the braking efficiency is increased from 55% to 58% of the test weight of the vehicle.
multiple	26, 27, 29 Exterior Lamps	Lamp switches are included in the test.
52	32, Auxiliary Lamp Condition and Position	Auxiliary lamps must operate independently of the side light(s).
multiple	35, 54 Bodywork and Exhaust system	Engine exhaust fumes entering the passenger compartment is a reason for failure.
62	37, Tyre Specification	A tyre not fit for purpose (e.g. marked "For Trailer Use Only" or similar) is a reason for failure.
multiple	43, 46, 55, 57 Steering Linkage, suspension and drivetrain	Missing dust cover is a reason for failure.
78	49, Electrical System	Damaged electrical wiring as opposed to wiring insulation is now a reason for failure.
89	58, Rear Fog Lamp(s)	Rear fog lamps and switches, where fitted must be working correctly.
91	60, Malfunction Indicators	Parking brake malfunction indicator check and the relevant reasons for failure has been added to the test.